

● Standard type model number list (spray angle: 15° to 80°, thread size: 1/8 to 1/4)

●: Model availability

Thread size	Model		Model number	Minimum orifice diameter [mm]	Flow rate [L/min] at following pressure [MPa]								Spray angle at following pressure [MPa]					
	Male	Female			0.05	0.1	0.2	0.3	0.5	0.7	1.0	1.5	0.1	0.2	0.3	0.5	1.0	1.5
	KSH	KSH+H																
1/8	●	●	00815	0.8	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	7°	12°	15°	17°	19°	19°
	●	●	00825	0.8	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	14°	21°	25°	28°	30°	30°
	●	●	00840	0.7	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	27°	35°	40°	44°	46°	46°
	●	●	00850	0.6	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	35°	45°	50°	54°	57°	57°
	●	●	00865	0.5	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	49°	59°	65°	70°	73°	73°
	●	●	00880	0.5	0.33	0.46	0.65	0.80	1.03	1.22	1.46	1.79	64°	74°	80°	85°	88°	88°
	●	●	01115	0.9	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	7°	12°	15°	17°	19°	19°
	●	●	01225	0.9	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	14°	21°	25°	28°	30°	30°
	●	●	0140	0.8	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	28°	36°	40°	44°	46°	46°
	●	●	0150	0.7	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	36°	45°	50°	54°	57°	57°
	●	●	0165	0.7	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	49°	59°	65°	70°	73°	73°
	●	●	0180	0.6	0.41	0.58	0.82	1.00	1.29	1.53	1.83	2.2	64°	74°	80°	85°	88°	88°
	●	●	01515	1.1	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	9°	13°	15°	17°	19°	19°
	●	●	01525	1.0	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	14°	21°	25°	28°	30°	30°
	●	●	01540	0.9	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	28°	36°	40°	44°	46°	46°
	●	●	01550	0.8	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	36°	45°	50°	54°	57°	57°
	●	●	01565	0.7	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	50°	59°	65°	70°	73°	73°
	●	●	01580	0.6	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	65°	74°	80°	85°	88°	88°
	●	●	0215	1.3	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	9°	13°	15°	17°	19°	19°
	●	●	0225	1.2	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	14°	21°	25°	28°	30°	30°
	●	●	0240	1.1	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	28°	36°	40°	44°	46°	46°
	●	●	0250	1.0	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	36°	45°	50°	54°	57°	57°
	●	●	0265	0.9	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	50°	59°	65°	70°	73°	73°
	●	●	0280	0.8	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	65°	74°	80°	85°	88°	88°
	●	●	0315	1.6	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	10°	13°	15°	17°	19°	19°
	●	●	0325	1.5	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	16°	22°	25°	28°	30°	30°
	●	●	0340	1.4	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	30°	37°	40°	44°	46°	46°
	●	●	0350	1.3	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	38°	45°	50°	54°	57°	57°
	●	●	0365	1.2	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	50°	59°	65°	70°	73°	73°
	●	●	0380	1.0	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	65°	74°	80°	85°	88°	88°
	●	●	0415	1.8	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	10°	13°	15°	17°	19°	19°
	●	●	0425	1.7	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	17°	22°	25°	28°	30°	30°
	●	●	0440	1.6	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	31°	37°	40°	44°	46°	46°
	●	●	0450	1.5	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	40°	46°	50°	54°	57°	57°
	●	●	0465	1.3	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	53°	60°	65°	70°	73°	73°
	●	●	0480	1.2	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	67°	75°	80°	85°	88°	88°
●	●	0615	2.2	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	10°	13°	15°	17°	19°	19°	
●	●	0625	2.1	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	17°	22°	25°	28°	30°	30°	
●	●	0640	2.0	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	31°	37°	40°	44°	46°	46°	
●	●	0650	1.9	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	40°	46°	50°	54°	57°	57°	
●	●	0665	1.7	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	53°	60°	65°	70°	73°	73°	
●	●	0680	1.5	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	67°	75°	80°	85°	88°	88°	
●	●	0815	2.6	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	10°	13°	15°	17°	19°	19°	
●	●	0825	2.5	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	17°	22°	25°	28°	30°	30°	
●	●	0840	2.3	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	31°	37°	40°	43°	45°	45°	
●	●	0850	2.2	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	40°	46°	50°	54°	56°	56°	
●	●	0865	2.0	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	53°	60°	65°	70°	72°	72°	
●	●	0880	1.8	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	67°	75°	80°	85°	87°	87°	
●	●	1015	3.1	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	10°	13°	15°	17°	19°	19°	
●	●	1025	2.9	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	17°	22°	25°	28°	30°	30°	
●	●	1040	2.7	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	31°	37°	40°	43°	45°	45°	
●	●	1050	2.5	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	40°	46°	50°	54°	56°	56°	
●	●	1065	2.3	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	54°	61°	65°	69°	71°	71°	
●	●	1080	2.0	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	68°	76°	80°	84°	85°	86°	
●	●	1515	3.8	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	10°	13°	15°	17°	19°	19°	
●	●	1525	3.6	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	17°	22°	25°	28°	30°	30°	
●	●	1540	3.4	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	31°	37°	40°	43°	45°	45°	
●	●	1550	3.2	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	40°	46°	50°	54°	56°	56°	
●	●	1565	2.9	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	54°	61°	65°	69°	71°	71°	
●	●	1580	2.6	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	68°	76°	80°	84°	86°	86°	

● Standard type model number list (spray angle: 15° to 80°, thread size: 1/4 to 1 1/2)

●: Model availability

Thread size	Model		Model number	Minimum orifice diameter [mm]	Flow rate [L/min] at following pressure [MPa]								Spray angle at following pressure [MPa]					
	Male	Female			0.05	0.1	0.2	0.3	0.5	0.7	1.0	1.5	0.1	0.2	0.3	0.5	1.0	1.5
	KSH	KSH-H																
1/4	●	●	2015	4.3	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	10°	13°	15°	17°	19°	19°
	●	●	2025	4.1	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	18°	22°	25°	28°	30°	30°
	●	●	2040	3.9	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	31°	37°	40°	43°	45°	45°
	●	●	2050	3.7	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	40°	46°	50°	54°	56°	56°
	●	●	2065	3.4	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	54°	61°	65°	69°	71°	71°
	●	●	2080	3.1	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	68°	76°	80°	84°	86°	86°
	●	●	2515	4.7	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	10°	13°	15°	17°	19°	19°
	●	●	2525	4.5	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	17°	22°	25°	28°	30°	30°
	●	●	2540	4.3	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	31°	37°	40°	43°	45°	45°
	●	●	2550	4.1	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	40°	46°	50°	54°	56°	56°
	●	●	2565	3.8	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	54°	61°	65°	69°	71°	71°
	●	●	2580	3.5	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	68°	76°	80°	84°	86°	86°
	●	●	3015	5.0	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	10°	13°	15°	17°	19°	19°
	●	●	3025	4.8	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	17°	22°	25°	28°	30°	30°
	●	●	3040	4.6	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	31°	37°	40°	43°	45°	45°
	●	●	3050	4.4	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	40°	46°	50°	54°	56°	56°
●	●	3065	4.2	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	54°	61°	65°	69°	71°	71°	
●	●	3080	3.9	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	68°	76°	80°	84°	86°	86°	
3/8	●	●	3515	5.4	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	10°	13°	15°	17°	19°	19°
	●	●	3525	5.2	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	17°	22°	25°	28°	30°	30°
	●	●	3540	5.0	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	31°	37°	40°	43°	45°	45°
	●	●	3550	4.8	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	40°	46°	50°	54°	56°	56°
	●	●	3565	4.5	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	54°	61°	65°	69°	71°	71°
	●	●	3580	4.3	14.3	20.2	28.6	35.0	45.2	53.5	63.9	78.3	68°	76°	80°	84°	86°	86°
	●	●	4015	5.9	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	10°	13°	15°	17°	19°	19°
	●	●	4025	5.7	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	17°	22°	25°	28°	30°	30°
	●	●	4040	5.4	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	31°	37°	40°	43°	45°	45°
	●	●	4050	5.2	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	41°	46°	50°	54°	56°	56°
1/2	●	●	4065	4.9	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	55°	61°	65°	69°	71°	71°
	●	●	4080	4.6	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	69°	76°	80°	84°	86°	86°
	●	●	5050	5.6	20.4	28.9	40.8	50.0	64.5	76.4	91.3	112	41°	46°	50°	53°	55°	55°
	●	●	5065	5.4	20.4	28.9	40.8	50.0	64.5	76.4	91.3	112	55°	61°	65°	68°	70°	70°
	●	●	5080	5.0	20.4	28.9	40.8	50.0	64.5	76.4	91.3	112	69°	76°	80°	83°	85°	85°
	●	●	6050	6.2	24.5	34.6	49.0	60.0	77.5	91.7	110	134	41°	46°	50°	53°	55°	55°
	●	●	6065	5.9	24.5	34.6	49.0	60.0	77.5	91.7	110	134	55°	61°	65°	68°	70°	70°
	●	●	6080	5.5	24.5	34.6	49.0	60.0	77.5	91.7	110	134	70°	76°	80°	83°	85°	85°
	●	●	7050	6.8	28.6	40.4	57.2	70.0	90.4	107	128	157	41°	46°	50°	53°	55°	55°
	●	●	7065	6.5	28.6	40.4	57.2	70.0	90.4	107	128	157	55°	61°	65°	68°	70°	70°
3/4	●	●	7080	6.1	28.6	40.4	57.2	70.0	90.4	107	128	157	70°	76°	80°	83°	85°	85°
	●	●	8050	7.5	32.7	46.2	65.3	80.0	103	122	146	179	41°	46°	50°	53°	55°	55°
	●	●	8065	7.1	32.7	46.2	65.3	80.0	103	122	146	179	55°	61°	65°	68°	70°	70°
	●	●	8080	6.7	32.7	46.2	65.3	80.0	103	122	146	179	70°	76°	80°	83°	85°	85°
	●	●	9050	8.0	36.7	52.0	73.5	90.0	116	137	164	201	41°	46°	50°	53°	55°	55°
	●	●	9065	7.6	36.7	52.0	73.5	90.0	116	137	164	201	55°	61°	65°	68°	70°	70°
	●	●	9080	7.1	36.7	52.0	73.5	90.0	116	137	164	201	70°	76°	80°	83°	85°	85°
	●	●	10050	8.5	40.8	57.7	81.6	100	129	153	183	224	42°	47°	50°	53°	54°	54°
	●	●	10065	8.0	40.8	57.7	81.6	100	129	153	183	224	57°	62°	65°	68°	69°	69°
	●	●	10080	7.5	40.8	57.7	81.6	100	129	153	183	224	72°	77°	80°	83°	84°	84°
1	●	●	15050	10.4	61.2	86.6	122	150	194	229	274	335	43°	47°	50°	53°	54°	54°
	●	●	15080	9.5	61.2	86.6	122	150	194	229	274	335	73°	77°	80°	83°	84°	84°
1 1/4	●	●	20050	12.6	81.6	115	163	200	258	306	365	447	43°	47°	50°	52°	53°	53°
	●	●	20080	11.0	81.6	115	163	200	258	306	365	447	73°	77°	80°	82°	83°	83°
1 1/4	●	●	25050	13.2	102	144	204	250	323	382	456	559	43°	47°	50°	52°	53°	53°
	●	●	25080	11.7	102	144	204	250	323	382	456	559	73°	77°	80°	82°	83°	83°
1 1/2	●	●	30050	14.1	122	173	245	300	387	458	548	671	45°	48°	50°	51°	52°	52°
	●	●	30080	12.5	122	173	245	300	387	458	548	671	75°	78°	80°	81°	82°	82°
1 1/2	●	●	35050	14.7	143	202	286	350	452	535	639	783	45°	48°	50°	51°	52°	52°
	●	●	35080	13.5	143	202	286	350	452	535	639	783	75°	78°	80°	81°	82°	82°
	●	●	40050	15.3	163	231	327	400	516	611	730	894	45°	48°	50°	51°	52°	52°
	●	●	40080	14.8	163	231	327	400	516	611	730	894	75°	78°	80°	81°	82°	82°

● Standard type model number list (spray angle: 95° to 110°, thread size: 1/8 to 1 1/2)

●: Model availability

Thread size	Model		Model number	Minimum orifice diameter [mm]	Flow rate [L/min] at following pressure [MPa]								Spray angle at following pressure [MPa]					
	Male KSH	Female KSH-H			0.05	0.1	0.2	0.3	0.5	0.7	1.0	1.5	0.1	0.2	0.3	0.5	1.0	1.5
1/8	●	●	01595	0.5	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	80°	89°	95°	100°	103°	103°
	●	●	015110	0.4	0.61	0.87	1.22	1.50	1.94	2.3	2.7	3.4	95°	104°	110°	115°	118°	118°
	●	●	0295	0.7	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	80°	89°	95°	100°	103°	103°
	●	●	02110	0.6	0.82	1.15	1.63	2.0	2.6	3.1	3.7	4.5	95°	104°	110°	115°	118°	118°
1/4	●	●	0395	0.9	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	80°	89°	95°	100°	103°	103°
	●	●	03110	0.8	1.22	1.73	2.4	3.0	3.9	4.6	5.5	6.7	95°	104°	110°	115°	118°	118°
	●	●	0495	1.0	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	80°	89°	95°	100°	103°	103°
	●	●	04110	0.9	1.63	2.3	3.3	4.0	5.2	6.1	7.3	8.9	95°	104°	110°	115°	118°	118°
	●	●	0695	1.2	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	80°	89°	95°	100°	103°	103°
	●	●	06110	1.1	2.4	3.5	4.9	6.0	7.7	9.2	11.0	13.4	95°	104°	110°	115°	118°	118°
	●	●	0895	1.5	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	81°	90°	95°	100°	102°	102°
	●	●	08110	1.4	3.3	4.6	6.5	8.0	10.3	12.2	14.6	17.9	96°	105°	110°	115°	117°	117°
	●	●	1095	1.7	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	81°	90°	95°	100°	102°	102°
	●	●	10110	1.6	4.1	5.8	8.2	10.0	12.9	15.3	18.3	22.4	96°	105°	110°	115°	117°	117°
	●	●	1595	2.3	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	82°	90°	95°	100°	102°	102°
	●	●	15110	2.0	6.1	8.7	12.2	15.0	19.4	22.9	27.4	33.5	97°	105°	110°	115°	117°	117°
●	●	2095	2.7	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	82°	90°	95°	100°	102°	102°	
●	●	20110	2.4	8.2	11.5	16.3	20.0	25.8	30.6	36.5	44.7	97°	105°	110°	115°	117°	117°	
3/8	●	●	2595	3.1	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	82°	90°	95°	100°	102°	102°
	●	●	25110	2.7	10.2	14.4	20.4	25.0	32.3	38.2	45.6	55.9	97°	105°	110°	115°	117°	117°
1/2	●	●	3095	3.5	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	82°	90°	95°	100°	102°	102°
	●	●	30110	3.0	12.2	17.3	24.5	30.0	38.7	45.8	54.8	67.1	97°	105°	110°	115°	117°	117°
	●	●	4095	4.1	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	83°	91°	95°	99°	101°	101°
	●	●	40110	3.6	16.3	23.1	32.7	40.0	51.6	61.1	73.0	89.4	98°	106°	110°	115°	117°	117°
	●	●	5095	4.5	20.4	28.9	40.8	50.0	64.5	76.4	91.3	112	83°	91°	95°	99°	101°	101°
	●	●	50110	4.0	20.4	28.9	40.8	50.0	64.5	76.4	91.3	112	98°	106°	110°	115°	117°	117°
	●	●	6095	5.1	24.5	34.6	49.0	60.0	77.5	91.7	110	134	84°	91°	95°	98°	100°	100°
●	●	60110	4.5	24.5	34.6	49.0	60.0	77.5	91.7	110	134	99°	106°	110°	113°	116°	116°	
3/4	●	●	7595	5.8	30.6	43.3	61.2	75.0	96.8	115	137	168	84°	91°	95°	98°	100°	100°
	●	●	75110	4.9	30.6	43.3	61.2	75.0	96.8	115	137	168	99°	106°	110°	113°	115°	115°
	●	●	10095	6.8	40.8	57.7	81.6	100	129	153	183	224	87°	92°	95°	97°	99°	99°
	●	●	100110	5.9	40.8	57.7	81.6	100	129	153	183	224	100°	107°	110°	112°	114°	114°
1	●	●	15095	8.5	61.2	86.6	122	150	194	229	274	335	87°	92°	95°	97°	99°	99°
	●	●	150110	7.3	61.2	86.6	122	150	194	229	274	335	100°	107°	110°	112°	114°	114°
	●	●	20095	10.8	81.6	115	163	200	258	306	365	447	88°	92°	95°	97°	98°	98°
	●	●	200110	10.1	81.6	115	163	200	258	306	365	447	103°	107°	110°	112°	113°	113°
1 1/4	●	●	30095	11.8	122	173	245	300	387	458	548	671	90°	93°	95°	96°	97°	97°
	●	●	300110	11.4	122	173	245	300	387	458	548	671	105°	108°	110°	111°	112°	112°
1 1/2	●	●	40095	14.5	163	231	327	400	516	611	730	894	90°	93°	95°	96°	97°	97°
	●	●	400110	14.1	163	231	327	400	516	611	730	894	105°	108°	110°	111°	112°	112°