

● Standard type model number list

Model	Model number	Minimum orifice diameter [mm]	Flow rate [L/min] at following pressure [MPa]								Spray angle at 0.5 MPa
			0.3	0.5	0.7	1.0	1.5	2.0	2.5	3.0	
KSC	005	0.6	0.50	0.65	0.76	0.91	1.12	1.29	1.44	1.58	60°
	008	0.7	0.80	1.03	1.22	1.46	1.79	2.1	2.3	2.5	
	01	0.9	1.00	1.29	1.53	1.83	2.2	2.6	2.9	3.2	
	015	1.0	1.50	1.91	2.3	2.7	3.3	3.8	4.3	4.7	
	018	1.2	1.80	2.3	2.8	3.3	4.0	4.7	5.2	5.7	
	02	1.3	2.0	2.6	3.1	3.7	4.5	5.2	5.9	6.4	
	025	1.4	2.5	3.3	3.9	4.6	5.6	6.5	7.3	8.0	
	03	1.5	3.0	3.9	4.6	5.5	6.7	7.8	8.7	9.5	
	035	1.5	3.5	4.5	5.4	6.4	7.8	9.1	10.1	11.1	
	04	1.6	4.0	5.2	6.1	7.3	8.9	10.3	11.5	12.6	
	045	1.6	4.5	5.8	6.9	8.2	10.0	11.6	13.0	14.2	
	05	1.7	5.0	6.4	7.6	9.1	11.2	12.9	14.4	15.8	
	06	1.8	6.0	7.8	9.2	11.0	13.5	15.6	17.4	19.0	