

● Standard type model number list (supply pressure : 3.5 MPa)

Model	Model number	Standard spray flow rate [L/h]	Minimum orifice diameter [mm]	Spray flow rate [L/min] at following return pressure [MPa]				Spray angle at following return pressure [MPa]				Sauter mean diameter [μm]
				1.35 ^{fully closeed}	1.0	0.6	0.2	1.35 ^{fully closeed}	1.0	0.6	0.2	
KSWC	141	3000	3.4	50.0	31.0	12.3	5.0	80°	86°	94°	100°	110
	188	4000	3.9	66.7	41.3	16.4	6.7	80°	86°	94°	100°	120
	283	6000	4.9	100	62.0	24.7	10.0	80°	86°	94°	100°	130
	377	8000	5.4	133	82.7	32.9	13.3	80°	86°	94°	100°	140
	471	10000	6.1	166	103	41.1	16.6	80°	86°	94°	100°	150
	566	12000	6.7	200	124	49.3	20.0	80°	86°	94°	100°	160
	707	15000	7.5	250	155	61.7	25.0	80°	86°	94°	100°	170
	800	17000	8.0	283	176	69.9	28.3	80°	86°	94°	100°	180
	943	20000	8.7	333	207	82.2	33.3	80°	86°	94°	100°	195
	1179	25000	9.7	416	258	103	41.6	80°	86°	94°	100°	210
	1414	30000	10.6	500	310	123	50.0	80°	86°	94°	100°	225
	1650	35000	11.5	583	362	144	58.3	80°	86°	94°	100°	240
	1886	40000	12.3	666	413	165	66.6	80°	86°	94°	100°	255

EVERLOY

<https://www.everloy-spray-nozzles.com>